

Pressure Tanks

Onga Aquapack Steel pressure tanks

Each pressure tank in the Onga range is constructed to store supply water under pressure to provide a buffer for your plumbing or piping, to minimise pump operation time and to maximise pump life. Onga has a wide range of pressure tanks to suit any needs. From the small Aquapack AP10 to the largest Sta-Rite Signature 2000, Onga offers a range from 3L to more than 450L.

Aquapack Range



The Onga Aquapack range starts with the moulded 3 litre AP10 and continues up to the AP80. The range includes specialist models like the corrosion-resistant AP50S in stainless steel, and the AP80HP for high pressure applications. There's a model to suit every application. Riva-flo 130 included in Aquapack range.

AP80HP



Onga also caters for high pressure applications such as multi-storey water supply or high pressure, deep well sites with the Aquapack AP80HP tank, rated to 1520kPa.

AP50S



The Stainless steel Aquapack AP50S provides a 24L tank constructed from 304 grade stainless steel. This gives it incredible corrosion resistance*.
* Not recommended for water with very high chloride levels.
In this case we recommend using a signature 2000 tank.

Pro-Source Range



The Pro-Source range offers large steel tanks for high volume applications – they make great partners for the 70–150 Lpm submersible pumps



Aquapack steel pressure tanks features

Replaceable bladders available	Extends the useful life of the product
Stainless steel inlet flange/connection	Corrosion resistance and strength at connection point
Wide range available	Optimise your pressure system

Pressure Switch Settings kPa	THEORETICAL DRAW OFF IN LITRES								
	AQUA PACK MODELS							PRO-SOURCE	
	10	18	50	50s	80	80HP	RF130	PS42T	PS80T
100 - 200	1.1	2.8	8	8	11.3	11.3	20.1	24.4	44.2
140 - 275	1.2	3	8.8	8.8	12.3	12.3	21.9	26.6	48.2
210 - 340	1	2.5	7	7.4	10.4	10.4	18.5	22.5	40.7
275 - 415	0.9	2.2	7.4	6.4	9	9	16	19.5	35.3
275 - 450		2.6	7.5	7.5	10.5	10.5	18.8	22.8	41.3
345 - 550		2.6			10.6	10.6	18	23	41.8
410 - 620		2.4			9.6	9.6	17.2	20.8	
480 - 690		2.2			8.8	8.8	15.7	19	
760 - 1000					8.2	8.2			
960 - 1240						6.9			
1100 - 1380						6.3			
Vol litres	3.2	8.2	24	24	34	34	60	72	133
Max Rating kPa	380	690	435	550	1000	1520	790	690	570
Dia (cm)	21	20	33	32	36	36	38	40	50
Height (cm)	24	33	38	37	40	40	85	78	87
Inlet size (BSP)	3/4"F	1"M	1"M	1"M	1"F	1"F	1"F	1"F	1"F
Weight (kg)	1.6	2.4	5.7	3.6	10.7	10.7	16	26	33
Warranty (yrs)	1	1	1	5	1	1	1	4	4

